

EN

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Hilti Firestop Mortar CFS-M RG

No. Hilti CFS "0761-CPD-0210"

1. Unique identification code of the product-type:

Hilti Firestop Mortar CFS-M RG

2. Type, batch or serial number as required pursuant to Article 11(4):

see batch number displayed on the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

Fire Stopping and Sealing Product for Penetration Seals, see ETA-12/0101

Cable penetrations	Cables, Cable bundles, Cable trays, Conduits	The field of application has to comply with the content of the related ETA and in connection with the additional components described in the related ETA.
Pipe penetrations	Metal and Plastic pipes	
Mixed penetrations	Cables, Cable trays, Metal and Plastic pipes	

4. Name, registered trade name or registered trade mark and contact address as required pursuant to Article 11(5):

HILTI Corporation, Feldkircherstrasse 100, 9494 Schaan, Principality of Liechtenstein

5. Authorised representative: n.a.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. Harmonised standard: n.a.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

OIB Austrian Institute of Construction Engineering issued European Technical Approval ETA-12/0101 on the basis of ETAG No. 026-1 and ETAG No. 026-2, the notified body MPA (Materialprüfanstalt für das Bauwesen) TU Braunschweig performed third party tasks as set out in Annex V under System 1 and issued Certification of Conformity 0761-CPD-0210.

9. Declared performance:

Essential characteristic	Declared performance / Harmonised technical specification
Reaction to fire	Class A1 according to EN 13501-1
Resistance to fire	Resistance to fire performance and field of application in accordance with EN 13501-2. See ETA-12/0101
Air permeability	Tested according to EN 1026. See ETA-12/0101
Dangerous substances	See ETA-12/0101, clause 2.5
Resistance to impact/movement	Tested according to EOTA Technical Report - TR001. See ETA-12/0101
Protection against noise	Tested according to EN ISO 717-1 and EN ISO 20140-10. See ETA-12/0101
Durability and serviceability	$Y_{1,(-5/+70)^{\circ}C}$ in accordance with EOTA Technical Report - TR024.
Thermal properties	Tested according to EN12667. See ETA-12/0101
Electrical properties	Tested according to DIN IEC 93 (VDE 0303 Part 30): 1993-12. See ETA-12/0101
Other	Not applicable / No performance determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Paul Langford
BU Head
Business Unit Chemicals
Hilti Corporation

Schaan, July 2013

Martin Althof
Head of Quality
Business Unit Chemicals
Hilti Corporation