

AL Hilti Albania Sh.p.k.
Ruga Dritan Hoxha, Laprake
AL-Tirane
Tel +355 4241 3906
Fax +355 4241 3909

BA Hilti Systems BH d.o.o.
Dobrinjska 7, BA-71000,
Sarajevo-lidža
Tel +387 33 761 100
Fax +387 33 761 101

BG Hilti (Bulgaria) Ltd.
Mladost 4, Business Park Sofia,
building 11A, floor 4
BG-1786 Sofia
Tel +359 2 974 01 23
Fax +359 2 974 01 23

GR Hilti Hellas SA
L. Kimis 132
GR-151 23 Marousi, Athens
Tel +30 210 288 0600
Fax +30 210 288 0607

HU Hilti (Hungária)
Szt. István krt. 17.
H-6000 Kecskemét
Tel +36 76 518 400
Fax +36 76 481 638

IL Hilti (Israel) Ltd.
6 Ravnitsky St. Ind. Zone Sgula
P.O.Box 2650
49125 Petach Tikva
Tel +972 3930 4499
Fax +972 3 930 2095


RO Hilti Romania S.R.L.
Parcul Industrial Bucharest West,
EQUEST LOGISTIC CENTRE
Comuna Dragomiresti-Vale, Sat
Dragomiresti-Deal
Strada DE 287/1
RO-077096 Judetul Ilfov
Tel +40 21 352 3000
Fax +40 21 350 5181

RS Hilti SMN d.o.o.
Banatska 83C, 11080 Zemun
Belgrade
Tel +381 11 6556896
Fax +381 11 6556896

HILTI

Hilti HIT-RE 10

Instruction for use **en**
Használati útmutató **hu**
Ръководство за обслужване **bg**
Instrucțiuni de folosire **ro**
Οδηγίες χρήσης **el**



580ml / 19.61 fl. oz
900g / 31.71 oz

	en	hu	bg	ro	el
	Dry concrete	Száraz beton	Сух бетон	Beton uscat	Στεγνό σκυρόδεμα
	Water saturated concrete	Vízzel telített beton	Наситен с вода бетон	Beton saturat cu apă	Σκυρόδεμα κορεσμένο με νερό
	Uncracked concrete	Nem repedt beton	Ненапукан бетон	Beton nefisurat	Σκυρόδεμα χωρίς ρηγματώσεις
	Threaded rod	Menetes rúd Menetes hüvely	Щанга с резба Втулка с резба	Tijă filetată Manșon filetat	Βέργα με σπείρωμα Χιτώνιο με σπείρωμα
	Rebar	Betonvas	Арматура	Armătură metalică	Σίδερο οπλισμού
	Hammer drilling	Ütvefűrés	Ударно пробиване	Găuire cu percucie	Κρουστική διάτρηση
	Working time	Feldolgozhatósági idő	Време за обработване	Timpul de prelucrare	Χρόνος επεξεργασίας
	Initial curing time	Rögzítési szilárdság	Здравина при монтаж	Stabilitatea la montaj	Αντοχή τοποθέτησης
	Curing time	Kikeményedési idő	Време на втвърдяване	Timpul de întărire	Χρόνος εφαρμογής φορτίων

Ø	HIT-V	Rebar	HIT-RB	HIT-VL HIT-SZ	HIT-DL
d _o [inch]	d _o [mm]	d [inch]	d [mm]	d [inch]	d [mm]
7/16	10	3/8	8	8	7/16
1/2	12	–	10	#3	8/10
9/16	14	1/2	12	10M	10/12
5/8	16	–	–	#4	12
11/16	18	–	16	–	14
3/4	20	5/8	–	15M #5	16
7/8	22	3/4	20	#6	18
1	25	7/8	–	20M #7	20
1 1/8	28	1	24	#8	22
–	30	–	27	–	–
1 1/4	32	–	–	25M	24/25
1 3/8	35	1 1/4	30	#9	26/28
1 1/2	37	–	–	30M #10	30
1 3/4	40	–	–	#11	32

HIT-DL: hef > 10" / 250mm HIT-RB: hef > 20 x d

www.hilti.group Made by Hilti in China
Hilti is registered trademark of Hilti Corporation, Schaan, Liechtenstein
© 2019
Right of technical changes reserved S.E. & O.

2153840 V7-06.2019

Danger
Contains: Epoxy resin (A), Amines (B)
Causes severe skin burns and eye damage (A, B). May cause an allergic skin reaction (A, B). Suspected of causing genetic defects (A). May damage fertility or the unborn child (A). Toxic to aquatic life with long lasting effects (A). Do not get in eyes, on skin, or on clothing. Wear eye protection, protective clothing, protective gloves.

HIT-RE-M Art. No.	HDE 500-A HDM 500	HIT-OHW Art. No.	HIT-OHC
337111		387550	387551 ≤ 20mm / 3/4" 387552 > 20mm / 3/4"

Ø	hef	Art. No.	
d _o [inch]	d _o [mm]	[inch]	[mm]
7/16...1 1/8	10...30	23/8...19 1/16	60...500
1 1/4...1 3/4	32...40	4 1/2...19 1/16	100...500
			≥ 90 psi/6 bar @ 6 m³/h
			≥ 140 m³/h / ≥ 82CFM

	[°F]	[°C]	t _{work}	t _{cure, ini}	t _{cure, full}
	41...50	5...10	5 h	30 h	72 h
	>50...68	>10...15	2.5 h	20 h	48 h
	>59...68	>15...20	2 h	15 h	36 h
	>68...86	>20...30	60 min	10 h	24 h
	>86...104	>30...40	30 min	5 h	12 h

≥ +10 °C / 50 °F

= 2x t_{cure}

HIT-V			
d [mm]	hef [mm]	df [mm]	T _{max} [mm]
8	60...160	9	10
10	60...200	12	20
12	70...240	14	40
–	–	–	–
16	80...320	18	80
20	90...400	22	150
24	96...480	26	200
27	108...500	30	270
30	120...500	33	300

Rebar	
d [mm]	hef [mm]
8	60...160
10	60...200
12	70...240
–	–
14	75...280
16	80...320
20	90...400
25	100...500
28	112...500
32	128...500

